



```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               *
* Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0,                               *
*                               *
*****

```

```

+++ P R O G R A M   P A R A M E T E R S +++
=====

```

Process is DEFAULT: Units Are Degrees, Feet, and Kips Unless Specified

```

Max. Length for Drag Comp.      =      20.000
Max. Area for Drag Comp.        =     400.000
Specific Gravity of Water       =       1.025
Acceleration of Gravity         =     32.200
Water Depth                     =       0.000
Added Mass Coef. for Tubes      =       0.800
Added Mass Coef. for Plates     =       0.376
Drag Coef. for Plates           =       1.000

```

NUMBER	COEFFICIENT
-----	-----
.10E+01	0.63
.10E+09	0.63

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, *
*                               *****                               *

```

+++ CATEGORY SUMMARY FOR SELECTED PARTS +++  
 =====

Process is DEFAULT: Units Are Degrees, Feet, and Kips Unless Specified

Results Are Reported In The Part System

Category	Weight Factor	Buoyancy Factor	Name	Weight	/--- Center of Gravity ---/			Buoyancy	/-- Center of Buoyancy --/		
					X	Y	Z		X	Y	Z
CARGO	1.000	1.000	CARGO	490.00	24.50	2.46	14.00	0.00	0.00	0.00	0.00
CREW	1.000	1.000	CREW	12.00	72.00	0.00	16.19	0.00	0.00	0.00	0.00
LEGS	1.000	1.000	C_PAD	26.08	97.25	0.00	-54.00	0.00	0.00	0.00	0.00
			P_PAD	26.08	24.00	-31.75	-54.00	0.00	0.00	0.00	0.00
			S_PAD	26.08	24.00	31.75	-54.00	0.00	0.00	0.00	0.00
			~LEG	478.92	48.42	0.00	46.75	615.31	48.42	0.00	46.75
L_SHIP	1.000	1.000	HULL	837.79	50.44	-1.28	9.08	0.00	0.00	0.00	0.00
VARIABLE	1.000	1.000	VARIABLE	391.00	59.61	0.01	15.03	0.00	0.00	0.00	0.00
TOTAL				2287.94	46.07	0.06	16.92	615.31	48.42	0.00	46.75

\*\*\*\*\*  
 \* \*\*\* MOSES \*\*\* \*  
 \* -----  
 \* January 13, 2003 \*  
 \* Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, \*  
 \* \*\*\*\*\*

+++ E X T E R N A L P I E C E S U M M A R Y +++  
 =====

Process is DEFAULT: Units Are Degrees, Feet, and Kips Unless Specified

Piece Name	Permeab.	Diffrac. Type	Wind Coefficients			Drag Coefficients			Projected Area			Sum Area * Normal		
			X	Y	Z	X	Y	Z	X	Y	Z	X	Y	Z
HULL	1.000	3DDif	1.00	1.00	1.00	1.00	1.00	1.00	667.	860.	5623.	-0.022	-0.007	0.000
JKTWR_P	0.000	None	0.64	0.64	0.00	0.00	0.00	0.00	84.	84.	28.	0.000	0.000	0.000
JKTWR_S	0.000	None	0.64	0.64	0.00	0.00	0.00	0.00	84.	84.	28.	0.000	0.000	0.000
JKTWR_C	0.000	None	0.64	0.64	0.00	0.00	0.00	0.00	84.	84.	28.	0.000	0.000	0.000
PH1	0.000	None	1.00	1.00	0.00	0.00	0.00	0.00	77.	3.	22.	0.000	0.000	0.000
PH2	0.000	None	1.00	1.00	0.00	0.00	0.00	0.00	179.	67.	114.	0.000	0.000	0.000
PH3	0.000	None	1.00	1.00	0.00	0.00	0.00	0.00	274.	56.	165.	0.000	0.000	0.000
PH4	0.000	None	1.00	1.00	0.00	0.00	0.00	0.00	227.	93.	368.	0.000	0.000	0.000
QTRS02	0.000	None	1.00	1.00	0.00	0.00	0.00	0.00	300.	233.	1008.	0.000	0.000	0.000
QTRS01	0.000	None	1.00	1.00	0.00	0.00	0.00	0.00	195.	206.	715.	0.000	0.000	0.000
CARGO	0.000	None	1.00	1.00	0.00	0.00	0.00	0.00	121.	162.	300.	0.000	0.000	0.000
KP_P_CRA	0.000	None	1.00	1.00	0.00	1.00	1.00	0.00	53.	53.	2.	0.000	0.000	0.000
PD_P_CRA	0.000	None	0.64	0.64	0.00	0.64	0.64	0.00	20.	20.	20.	0.000	0.000	0.000
CB_P_CRA	0.000	None	1.00	1.00	0.00	1.00	1.00	0.00	56.	56.	44.	0.000	0.000	0.000
KP_S_CRA	0.000	None	1.00	1.00	0.00	1.00	1.00	0.00	5.	5.	0.	0.000	0.000	0.000
PD_S_CRA	0.000	None	0.64	0.64	0.00	0.64	0.64	0.00	9.	9.	7.	0.000	0.000	0.000
CB_S_CRA	0.000	None	1.00	1.00	0.00	1.00	1.00	0.00	9.	9.	7.	0.000	0.000	0.000
P_CRANE	0.000	None	0.60	0.60	0.60	0.00	0.00	0.00	203.	455.	734.	-101.336	909.008	1461.169
S_CRANE	0.000	None	0.60	0.60	0.60	0.00	0.00	0.00	18.	41.	66.	-36.581	73.818	131.613

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               *                               *
* Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0,                               *
*                               *                               *
*****

```

+++ P A R A M E T E R S U M M A R Y +++  
=====

Weights  
=====

Variable = 391.00 Kips  
Variable CG = 59.61 Feet  
Cargo = 490.00 Kips  
Cargo CG = 24.50 Feet

Safety Factor  
=====

Safety Factor = 3.00

Jacks  
=====

Holding/Leg = 1052.04 Kips  
Jacking/Leg = 789.00 Kips

Environment  
=====

Wave Height = 0.00 Feet  
Wave Period = 8.00 Seconds  
Wave Crest = 0.00 Feet  
Surface Current = 5.07 Feet/Second  
Wind Speed = 50.00 Knots  
Water depth = 50.00 Feet  
Penetration = 4.00 Feet

Geometry (in feet)  
=====

Air Gap = 0.00  
Leg length = 200.00  
Top Guide = 18.50  
Bottom Guide = 1.50  
Leg Element Len = 11.10  
Leg Above JH = 127.50  
Active Leg Len = 55.50  
Buckling K factor = 1.72

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               *                               *
* Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0,                               *
* Forces Due to Null Environment                               *
*                               *                               *
*****

```

+++ F O R C E S   A C T I N G   O N   H U L L +++  
=====

Process is DEFAULT: Units Are Degrees, Feet, and Kips Unless Specified

Results Are Reported In Body System

Type of Force	X	Y	Z	MX	MY	MZ
Weight	0.0	0.0	-2287.9	-137.	105410.	0.
Buoyancy	0.0	0.0	164.9	0.	-7984.	0.
Applied	-500.0	0.0	0.0	0.	-7515.	5.
	=====	=====	=====	=====	=====	=====
Total	-500.0	0.0	-2123.0	-137.	89912.	5.

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               *
* Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0,                               *
* Forces Due to Environment 000 Deg from Stern                               *
*                               *
*****

```

+++ F O R C E S   A C T I N G   O N   H U L L +++

Process is DEFAULT: Units Are Degrees, Feet, and Kips Unless Specified

Results Are Reported In Body System

Type of Force	X	Y	Z	MX	MY	MZ
Weight	0.0	0.0	-2287.9	-137.	105410.	0.
Buoyancy	0.0	0.0	164.9	0.	-7984.	0.
Applied	-500.0	0.0	0.0	0.	-7515.	5.
	=====	=====	=====	=====	=====	=====
Total	-500.0	0.0	-2123.0	-137.	89912.	5.

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, *
*                               *****                               *

```

+++ R E S T R A I N T L O A D S +++  
=====

Units Are KSI, Degrees, Feet, and Kips Unless Specified

FX Intensity For Most Severe Load Case with Forces Greater Than 0

Element	/-- Node Names -/	Class	Case	/----- Force -----/			/----- Moment -----/		
				X	Y	Z	X	Y	Z
FIX	*LC6	~FIX	DIR_000	185.14	-0.04	184.65	0.16	520.11	-0.10
FIX 0035	*LP6	~FIX	DIR_000	157.40	0.86	967.04	-0.70	523.56	-0.06
FIX 0036	*LS6	~FIX	DIR_000	157.45	-0.82	971.35	0.62	523.73	-0.14

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, *
*                               *****                               *

```

```

+++ R E S T R A I N T   E N V E L O P E +++
=====

```

Units Are KSI, Degrees, Feet, and Kips Unless Specified

Element	/-- Node Names -/	Class	/----- Force -----/			/----- Moment -----/		
			X	Y	Z	X	Y	Z
FIX	*LC6	~FIX	185.14	-0.04	184.65	0.16	520.11	-0.10
			185.14	-0.04	184.65	0.16	520.11	-0.10
FIX 0035	*LP6	~FIX	157.40	0.86	967.04	-0.70	523.56	-0.06
			157.40	0.86	967.04	-0.70	523.56	-0.06
FIX 0036	*LS6	~FIX	157.45	-0.82	971.35	0.62	523.73	-0.14
			157.45	-0.82	971.35	0.62	523.73	-0.14

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, *
*                               *****                               *

```

+++ R E S T R A I N T L O A D S +++  
=====

Units Are KSI, Degrees, Feet, and Kips Unless Specified

FX Intensity For Most Severe Load Case with Forces Greater Than 0

Element	/-- Node Names -/	Class	Case	/----- Force -----/			/----- Moment -----/		
				X	Y	Z	X	Y	Z
FIX	*LC6	~FIX	DIR_000	185.14	-0.04	184.65	0.16	520.11	-0.10
FIX 0035	*LP6	~FIX	DIR_000	157.40	0.86	967.04	-0.70	523.56	-0.06
FIX 0036	*LS6	~FIX	DIR_000	157.45	-0.82	971.35	0.62	523.73	-0.14

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, *
*                               *****                               *

```

```

+++ R E S T R A I N T   E N V E L O P E +++
=====

```

Units Are KSI, Degrees, Feet, and Kips Unless Specified

Element	/-- Node Names -/	Class	/----- Force -----/			/----- Moment -----/		
			X	Y	Z	X	Y	Z
FIX	*LC6	~FIX	185.14	-0.04	184.65	0.16	520.11	-0.10
			185.14	-0.04	184.65	0.16	520.11	-0.10
FIX 0035	*LP6	~FIX	157.40	0.86	967.04	-0.70	523.56	-0.06
			157.40	0.86	967.04	-0.70	523.56	-0.06
FIX 0036	*LS6	~FIX	157.45	-0.82	971.35	0.62	523.73	-0.14
			157.45	-0.82	971.35	0.62	523.73	-0.14

\*\*\*\*\*  
 \* \*\*\* MOSES \*\*\* \*  
 \* ----- \*  
 \* January 13, 2003 \*  
 \* Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, \*  
 \* \*\*\*\*\*

+++ B E A M L O A D S +++  
 =====

Units Are KSI, Degrees, Feet, and Kips Unless Specified

Axial Intensity For Most Severe Load Case with Forces Greater Than 0

Element	-- Node	Names -/	Class	Case	Distance (in)	Axial Load	/----- Shear -----/	Torque	/----- Moments -----/		
							Y Z		Y Z		
LC1	*LC0	*LC1	~LEG	DIR_000	221.99	-195.65	0.16	-527.31	0.13	-9755.25	-2.16
LC2	*LC1	*LC2	~LEG	DIR_000	133.19	-204.44	-0.04	185.14	0.10	-7700.19	-1.70
LC3	*LC2	*LC3	~LEG	DIR_000	133.19	-213.23	-0.04	185.14	0.10	-5645.11	-1.23
LC4	*LC3	*LC4	~LEG	DIR_000	133.19	-222.03	-0.04	185.14	0.10	-3590.03	-0.77
LC5	*LC4	*LC5	~LEG	DIR_000	133.19	-230.82	-0.04	185.14	0.10	-1534.96	-0.31
LC6	*LC5	*LC6	~LEG	DIR_000	133.19	-239.62	-0.04	185.14	0.10	520.12	0.16
LCT	*LCT	*LC0	~LEG	DIR_000	1529.99	-101.01	0.00	0.00	0.00	0.00	0.00
LP1	*LP0	*LP1	~LEG	DIR_000	221.99	-978.04	591.49	-2.54	-479.62	-46.99	-8212.32
LP2	*LP1	*LP2	~LEG	DIR_000	133.19	-986.83	-157.40	0.86	0.06	-37.45	-6465.16
LP3	*LP2	*LP3	~LEG	DIR_000	133.19	-995.63	-157.40	0.86	0.06	-27.91	-4717.96
LP4	*LP3	*LP4	~LEG	DIR_000	133.19	-1004.42	-157.40	0.86	0.06	-18.38	-2970.79
LP5	*LP4	*LP5	~LEG	DIR_000	133.19	-1013.21	-157.40	0.86	0.06	-8.84	-1223.61
LP6	*LP5	*LP6	~LEG	DIR_000	133.19	-1022.01	-157.40	0.86	0.06	0.70	523.55
LPT	*LPT	*LP0	~LEG	DIR_000	1529.99	-101.01	0.00	0.00	0.00	0.00	0.00
LS1	*LS0	*LS1	~LEG	DIR_000	221.99	-982.35	591.68	2.42	479.78	44.75	-8215.02
LS2	*LS1	*LS2	~LEG	DIR_000	133.19	-991.14	-157.46	-0.82	0.14	35.68	-6467.27
LS3	*LS2	*LS3	~LEG	DIR_000	133.19	-999.94	-157.46	-0.82	0.14	26.60	-4719.51
LS4	*LS3	*LS4	~LEG	DIR_000	133.19	-1008.73	-157.45	-0.82	0.14	17.53	-2971.77
LS5	*LS4	*LS5	~LEG	DIR_000	133.19	-1017.52	-157.45	-0.82	0.14	8.45	-1224.01
LS6	*LS5	*LS6	~LEG	DIR_000	133.19	-1026.32	-157.45	-0.82	0.14	-0.62	523.73
LST	*LST	*LS0	~LEG	DIR_000	1529.99	-101.01	0.00	0.00	0.00	0.00	0.00

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, *
*                               *****                               *

```

```

+++ J O I N T   D I S P L A C E M E N T S +++
=====

```

In Body Part System

Node Name	Load Case	/----- Deflection (in) -----/			/----- Rotation (Deg) -----/		
		X	Y	Z	X	Y	Z
*LC1	DIR_000	-10.55130	0.00331	-0.02468	-0.00011	-0.25843	0.00026
	NULL	-10.55130	0.00331	-0.02468	-0.00011	-0.25843	0.00026
*LP1	DIR_000	-10.55034	-0.00135	-0.11341	-0.00307	-0.23332	0.00016
	NULL	-10.55034	-0.00135	-0.11341	-0.00307	-0.23332	0.00016
*LS1	DIR_000	-10.55379	0.00001	-0.11390	0.00304	-0.23339	0.00036
	NULL	-10.55379	0.00001	-0.11390	0.00304	-0.23339	0.00036

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               *                               *
* Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0,                               *
*                               *                               *
*****

```

```

+++ S E L E C T E D   V A L U E S +++
=====

```

Distance	DIR_000:Axi	DIR_000:VY	DIR_000:VZ	DIR_000:Tor	DIR_000:MY	DIR_000:MZ
0.001	-978.040	-157.401	0.859	0.061	-46.989	-8212.049
0.001	-978.040	-157.401	0.859	0.061	-46.988	-8211.982
5.550	-982.436	-157.401	0.859	0.061	-42.220	-7338.604
11.099	-986.832	-157.401	0.859	0.061	-37.452	-6465.160
11.100	-986.833	-157.405	0.859	0.061	-37.450	-6464.893
16.649	-991.230	-157.405	0.859	0.061	-32.682	-5591.429
22.198	-995.626	-157.405	0.859	0.061	-27.913	-4717.964
22.199	-995.628	-157.403	0.859	0.061	-27.912	-4717.708
27.748	-1000.024	-157.403	0.859	0.061	-23.143	-3844.251
33.298	-1004.420	-157.403	0.859	0.061	-18.375	-2970.795
33.298	-1004.421	-157.403	0.859	0.061	-18.374	-2970.520
38.848	-1008.818	-157.403	0.859	0.061	-13.605	-2097.063
44.397	-1013.214	-157.403	0.859	0.061	-8.837	-1223.607
44.398	-1013.215	-157.402	0.859	0.061	-8.835	-1223.348
49.947	-1017.612	-157.402	0.859	0.061	-4.067	-349.898
55.496	-1022.008	-157.402	0.859	0.061	0.702	523.552

```

*****
*                               *** MOSES ***                               *
*                               -----                               *
*                               January 13, 2003                               *
*                               Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, *
*                               *****                               *

```

```

+++ C O D E +++
=====

```

Check

```

Check Length      = 52.1697
Buckling K factor = 1.72
K1                = 89.73189
Rotational Stiff  = 2.5e4 k-ft/rad

```

\*\*\*\*\*  
 \* \*\*\* MOSES \*\*\* \*  
 \* -----  
 \* January 13, 2003 \*  
 \* Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0, \*  
 \* Length Used for Check = 52.1697, Rot\_stif = 2.5e4 k-ft/rad \*  
 \* \*\*\*\*\*

+++ S T A N D A R D W S B E A M C H E C K +++

Units Are KSI, Degrees, Feet, and Kips Unless Specified

Stresses For Most Severe Load Case with Unity Ratios Greater Than 0

Element	Node	Names	Class	Case	/- KL/R -/-		Distance (in)	/----- Stresses/Allowable (Ksi) -----/						API Unity Check	Comments
					Mom	AMF		Y-	Z-	Y-	Z-	Y-	Z-		
LC1	*LC0	*LC1	~LEG	DIR_000	54.8	61.1	222.0	-0.97	-40.47	0.01	0.00	-6.33	0.82	Eq H1-3	
					1.159	1.155		33.53	51.11	51.11	31.20	31.20			
LC2	*LC1	*LC2	~LEG	DIR_000	54.8	61.1	0.0	-0.97	-40.47	0.01	0.00	2.22	0.82	Eq H1-3	
					1.159	1.155		33.53	51.11	51.11	31.20	31.20			
LC3	*LC2	*LC3	~LEG	DIR_000	54.8	61.1	0.0	-1.01	-31.94	0.01	0.00	2.22	0.66	Eq H1-3	
					1.158	1.154		33.53	51.11	51.11	31.20	31.20			
LC4	*LC3	*LC4	~LEG	DIR_000	54.8	61.1	0.0	-1.05	-23.42	0.01	0.00	2.22	0.49	Eq H1-3	
					1.157	1.153		33.53	51.11	51.11	31.20	31.20			
LC5	*LC4	*LC5	~LEG	DIR_000	54.8	61.1	0.0	-1.10	-14.89	0.00	0.00	2.22	0.32	Eq H1-3	
					1.156	1.152		33.53	51.11	51.11	31.20	31.20			
LC6	*LC5	*LC6	~LEG	DIR_000	54.8	61.1	0.0	-1.14	-6.37	0.00	0.00	2.22	0.16	Eq H1-3	
					1.156	1.151		33.53	51.11	51.11	31.20	31.20			
LCT	*LCT	*LC0	~LEG	DIR_000	54.8	61.1	1530.0	-0.50	0.00	0.00	0.00	0.00	0.01	Eq H1-3	
					1.167	1.165		33.53	51.11	51.11	31.20	31.20			
LP1	*LP0	*LP1	~LEG	DIR_000	54.8	61.1	222.0	-4.83	-0.19	42.37	7.10	-0.03	0.97	Eq H1-3	
					1.088	1.067		33.53	51.11	51.11	31.20	31.20			
LP2	*LP1	*LP2	~LEG	DIR_000	54.8	61.1	0.0	-4.83	-0.19	42.37	-1.89	0.01	0.97	Eq H1-3	
					1.088	1.067		33.53	51.11	51.11	31.20	31.20			
LP3	*LP2	*LP3	~LEG	DIR_000	54.8	61.1	0.0	-4.87	-0.16	33.35	-1.89	0.01	0.80	Eq H1-3	
					1.088	1.066		33.53	51.11	51.11	31.20	31.20			
LP4	*LP3	*LP4	~LEG	DIR_000	54.8	61.1	0.0	-4.92	-0.12	24.34	-1.89	0.01	0.62	Eq H1-3	
					1.087	1.065		33.53	51.11	51.11	31.20	31.20			
LP5	*LP4	*LP5	~LEG	DIR_000	54.8	61.1	0.0	-4.96	-0.08	15.33	-1.89	0.01	0.45	Eq H1-3	
					1.086	1.064		33.53	51.11	51.11	31.20	31.20			
LP6	*LP5	*LP6	~LEG	DIR_000	54.8	61.1	0.0	-5.00	-0.04	6.31	-1.89	0.01	0.27	Eq H1-3	
					1.085	1.063		33.53	51.11	51.11	31.20	31.20			
LPT	*LPT	*LP0	~LEG	DIR_000	54.8	61.1	1530.0	-0.50	0.00	0.00	0.00	0.00	0.01	Eq H1-3	
					1.167	1.165		33.53	51.11	51.11	31.20	31.20			
LS1	*LS0	*LS1	~LEG	DIR_000	54.8	61.1	222.0	-4.85	0.19	42.38	7.11	0.03	0.97	Eq H1-3	
					1.088	1.067		33.53	51.11	51.11	31.20	31.20			
LS2	*LS1	*LS2	~LEG	DIR_000	54.8	61.1	0.0	-4.85	0.19	42.38	-1.89	-0.01	0.97	Eq H1-3	
					1.088	1.067		33.53	51.11	51.11	31.20	31.20			
LS3	*LS2	*LS3	~LEG	DIR_000	54.8	61.1	0.0	-4.89	0.15	33.36	-1.89	-0.01	0.80	Eq H1-3	
					1.087	1.066		33.53	51.11	51.11	31.20	31.20			
LS4	*LS3	*LS4	~LEG	DIR_000	54.8	61.1	0.0	-4.94	0.11	24.35	-1.89	-0.01	0.62	Eq H1-3	
					1.087	1.065		33.53	51.11	51.11	31.20	31.20			
LS5	*LS4	*LS5	~LEG	DIR_000	54.8	61.1	0.0	-4.98	0.07	15.33	-1.89	-0.01	0.45	Eq H1-3	
					1.086	1.064		33.53	51.11	51.11	31.20	31.20			
LS6	*LS5	*LS6	~LEG	DIR_000	54.8	61.1	0.0	-5.02	0.04	6.31	-1.89	-0.01	0.27	Eq H1-3	
					1.085	1.063		33.53	51.11	51.11	31.20	31.20			
LST	*LST	*LS0	~LEG	DIR_000	54.8	61.1	1530.0	-0.50	0.00	0.00	0.00	0.00	0.01	Eq H1-3	
					1.167	1.165		33.53	51.11	51.11	31.20	31.20			

Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0,



Rotational Spring Co \* 10\*\*3

```

*****
*                                     *** MOSES ***                               *
*                                     -----                               *
*                                     January 13, 2003                               *
*      Choctaw Cargo = 490, Water Depth = 50, Air Gap = 0,                               *
*                                                                                               *
*****

```

+++ I N D E X O F O U T P U T +++  
=====

PROGRAM PARAMETERS . . . . .	2
CATEGORY SUMMARY FOR SELECTED PARTS . . . . .	3
EXTERNAL PIECE SUMMARY . . . . .	4
PARAMETER SUMMARY . . . . .	5
FORCES ACTING ON HULL . . . . .	6
RESTRAINT LOADS . . . . .	8
RESTRAINT ENVELOPE . . . . .	9
RESTRAINT LOADS . . . . .	10
RESTRAINT ENVELOPE . . . . .	11
BEAM LOADS . . . . .	12
JOINT DISPLACEMENTS . . . . .	13
SELECTED VALUES . . . . .	14
CODE . . . . .	15
STANDARD WS BEAM CHECK . . . . .	16
INDEX OF OUTPUT . . . . .	18